

MA3-PS-4812

Modular Matrix PoE Power Supply



MA3-PS-4812 is a power supply for compatible modular matrices, enabling their PoE power delivery on compatible extension ports of matrix cards for remote powering of their connected devices, such as transmitters and receivers, to ease their installation

FEATURES

Easy to Install - Fits in a 1U space in a 19" rack above MTX3-34-M/VS-34FD



TECHNICAL SPECIFICATIONS

Power Supply: 48V 12A

Source: 100-240V AC 50/60Hz (recieves power via MTX3-34-M/VS-34FD)

Consumption: 5.2A

Environmental Conditions

Operating Temperature: 0° to +35°C (32° to 95°F)

Storage Temperature: -20° to +60°C (-4° to 140°F)

Humidity: 20% to 90%, RHL non-condensing

General Size: 1U (H), 19" (W)

Product Dimensions: 48.2cm x 13.8cm x 4.6cm (19" x 5.4" x 1.8") W, D, H

Product Weight: 2.6kg (5.7lbs) approx

Shipping Dimensions: 55cm x 27.7cm x 10.5cm (21.6" x 10.9" x 4.1") W, D, H

Shipping Weight: 3.3kg (7.2lbs) approx

Product Dimensions 48.20cm x 13.80cm x 4.60cm (18.98" x 5.43" x 1.81") W, D, H

Product Weight 2.6kg (5.7lbs) approx

Shipping Dimensions $55.00cm \times 27.70cm \times 10.50cm (21.65" \times 10.91" \times 4.13") W, D, H$

Shipping Weight 3.3kg (7.2lbs) approx