



MERO 6

6" High-end slim in-wall speaker

► Features

- High-end 2-way in-wall speaker
- Slim grill with thin border (1 mm)
- Elegant & unobtrusive design
- Warm & true to nature sound
- Paintable front grill
- 1" + 6" aluminum membrane drivers
- 60 Watt RMS power
- Gold plated spring clamp connectors
- Quick and simple mounting

► Applications

- Residential Hi-Fi & home cinema
- Retail stores & shopping centers
- Restaurants
- Lounges & bars
- Boutiques
- Offices



The MERO speakers will blend beautifully into any interior due to their nearly invisible design, making only their extraordinary sound draw your attention. Their slim grill with very thin border of only 1 mm and limited grill depth extrudes the surface by only 3.2 mm when installed.

Their grilles are retained by neodymium magnets which enables assembly in seconds, while powerful enough to keep the grill fixed, even when subject to vibrations or if touched. Their applications range from residential Hi-Fi and home cinema installations to multi-zone systems, unobtrusive installations in lounges, bars, boutiques and offices.

The selection of high-grade materials in combination with accurate acoustics craftsmanship makes the MERO speakers superior in their class. The largest sized MERO6 consists of a 6" aluminum cone woofer and complementary 1" dome tweeter that are smoothly matched and optimized using a high-quality crossover network. This results in a true to nature sound reproduction for a warm and detailed sound with an RMS power of 60 Watt.

An acoustically optimized waveguide matches the dispersion of woofer and tweeter, while a phaseplug reduces diffraction and enhances off-axis high frequency response. All these details share their part to its pure sound.

An elegant look with minimal visual impact is created by the slim grill with very thin border, while great ease and installers convenience is guaranteed using the quick-fix mechanism with Gold-CON™ connectivities. Installation can be done both vertically and horizontally, while the adjustable tweeter allows optimal orientation positioning.

► Specifications

SYSTEM SPECIFICATIONS		
Speaker type	2-way	
Max power	120 Watt	
RMS power	60 Watt	
Impedance	8 Ohm	
Sensitivity (1W/1m)	88 dB	
Sound pressure (max W/1m)	106 dB	
Frequency response (±3 dB)	55 Hz - 20 kHz	
Crossover frequency	3 kHz	
Crossover type	Passive built-in	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	196,5 x 276,5 x 82 mm	
Weight net	1.66 Kg	
Connection	Gold-Con™ spring clamps	
Drivers (coaxial)	HF	1" aluminium membrane
	LF	6" aluminium membrane
Construction	High quality ABS housing	
Grill Type	Thin edged white grill	
Cut-out measurement	174 x 254 mm	
Built-in depth	78,5 mm	
Mounting & handling	4 Screw quick-fixing mechanism	
Available colours	Black frame & white grill	
SHIPPING & ORDERING		
Packaging	Carton box	
Shipping weight & volume	2.1 Kg ~ 0.0083 Cbm	
Accessories included	Cut-out template	
Optional accessories	WTR24 24W 100V line transformer	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		

► Architects' and Engineers' Specifications

The in-wall loudspeaker shall be a 2-way type, equipped with a 6" aluminum cone low frequency driver and a 1" aluminum dome tweeter with neodymium magnet.

It shall have an RMS power handling of 60 Watt with a maximum power handling of 120 Watt and the frequency response (± 3 dB) shall range from 55 Hz to 20 kHz. The sensitivity shall be 88 dB when measuring with an input signal of 1 Watt at a distance of 1 meter, while the maximum continuous sound pressure level shall be 106 dB.

The loudspeaker shall have an impedance of 8 Ohm and shall contain a passive built-in crossover network with crossover frequency of 3000 Hz, which is constructed of high-quality components.

The speakers frame and basket shall be constructed as one entity in strong ABS with a black colour and a textured matt surface finishing. A 4-screw quick-fixing mechanism shall be provided to mount the speaker into a wall in a quick and simple way. The connectives shall be performed using Gold-Con™ spring clamp connectors.

To make the loudspeaker nearly invisible when mounted, the speaker shall have a white grill with a very thin border of 1 mm which extrudes the ceiling surface by only 3.2 mm. This grill shall be constructed of steel which can be painted to make it blend in with any environment. The assembly and disassembly of the grill shall be very simple thanks to the neodymium magnets that hold it in place.

The speaker shall have a width of 196,5 mm, a height of 276,5 mm and a depth of 82 mm and shall not exceed 1,66 kg. The speaker shall fit in a mounting hole of 174 mm x 254 mm and a build-in depth of 78,5 mm.

► Technical drawing

