

Highlights:

- Highflex™ solid & flexible jacket
- 2.5 mm² (13 AWG) thin and dense stranded conductors
- 11 mm (Ø) outer diameter
- Oxygen free copper
- Neutrik NL4FXX-W-S connectors by Neutrik
- Transparent shrink sleeve

Product information:

The PRA524 is a high quality loudspeaker cable constructed using the PLH425 cable and fitted with two Neutrik 4 pole speakON cable (NL4FXX-W-S) connectors. The cable consists of four 2.5 mm² (13 AWG) thin and dense stranded conductors. The combination of thin and dense strands with high purity oxygen free copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket of 11 mm provides great ease of installation for fixed systems while having perfect rolling & unrolling performance for highly demanding Rental & MI applications. An attached shrink sleeve allows custom labeling for easy identification. The cable comes in different lengths from 1.5 meters to 20 meters.

Components:

- Connector: NL4FXX-W - Neutrik speakON 4 pole cable connector



Certification:



Properties:



Product Features:

Series	Prime Series
Application	Rental & MI

Physical Characteristics:

Type of cable		4-core loudspeaker cable	
Inner conductor	Material	BC 224 x 0.12 mm (Ø) (OFC)	
	Section	2.5 mm²	
	Insulation	Material	PVC 3.2 mm (Ø)
		Colours	Black / Red / Blue / Yellow
Number of conductors		4	
American Wire Gauge		13 AWG	
Fitted connectors		2 x Neutrik NL4FXX-W-S	
Connection type		SpeakON Female to Female	
Outer jacket	Material	Durable PVC 11 mm (Ø)	
	Colours	Black	

Mechanical Characteristics:

Temperature range	Fixed installation	- 20 °C till + 70 °C
	Mobile installation	- 5 °C till + 70 °C
Bending radius	Fixed installation	5 x outer diameter
	Mobile installation	10 x outer diameter

Electrical Characteristics:

Lead resistance	0.8 Ω / 100 m
-----------------	---------------

Variants:

- PRA524/1.5 - 1.5 meter
- PRA524/3 - 3 meters
- PRA524/5 - 5 meter
- PRA524/10 - 10 meter
- PRA524/15 - 15 meter
- PRA524/20 - 20 meter