

Highlights:

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- 7.5 mm (Ø) outer diameter
- Oxygen free copper
- Double Al-foil shielding

CLV114 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. It has a aluminium foil shielding with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected.

Components:

- CableType: SVGA214 - Video Cable



Properties:



Usage:



Physical Characteristics:

| | | | |
|-------------------|---------------------|----------------|--|
| Inner conductor | Insulation | Material | FPE 1.55 mm (Ø) |
| | | Colours | White |
| | Shielding | Aluminium foil | Al-mylar, 100% coverage - 25% Overlap |
| | | Drain wire | BC 7 x 0.12 mm (Ø) (OFC) |
| | Insulation | Material | PVC 0.9 mm (Ø) |
| | | | PVC 1 mm (Ø) |
| | | Colours | Black |
| | | Material | PVC 0.9 mm (Ø) |
| | | Colours | Green / Blue ; Orange / Yellow ; Brown / Red |
| Overall shielding | Aluminium foil | | Al-mylar, 100% coverage - 25% Overlap |
| | Drain wire | | BC 7 x 0.16 mm (Ø) (OFC) |
| Outer jacket | Material | | PVC 7.5 mm (Ø) |
| | Colours | | Black |
| Type of cable | | | 75 Ω VGA video cable |
| Inner conductor | Material | | BC 7 x 0.12 mm (Ø) (OFC) |
| | | | BC 10 x 0.12 mm (Ø) (OFC) |
| | | | BC 10 x 0.12 mm (Ø) (OFC) |
| Filling | | | Cotton Yarn |
| Inner conductor | American Wire Gauge | | 28 AWG |

Variants:

- CLV114/1.5 - 1,5 meter
- CLV114/3 - 3 meter
- CLV114/5 - 5 meter
- CLV114/7.5 - 7.5 meter
- CLV114/10 - 10 meter
- CLV114/15 - 15 meter
- CLV114/25 - 25 meter
- CLV114/30 - 30 meter