


### Product information

The HDM24 is a bulk reel of quality 24AWG-size HDMI cable. Since this thicker cable offers less resistance, it is highly suitable for relatively longer distances. It is designed for installation using the PROCAB contractor series equipment. Lengths below 10m will perform as HIGH SPEED HDMI with ETHERNET. Lengths between 10 and 15m will perform at STANDARD SPEED HDMI with ETHERNET standards.

Recommended HD distance : 20 m (1080p)

### Highlights


- Triple shielding



### Certification



### Properties



### Inner Conductors



STRANDED TINNED COPPER



STRANDED OXYGEN FREE COPPER

### Shielding



TINNED COPPER BRAIDING



ALUMINUM FOIL



BARE COPPER DRAIN WIRE

### Usage

MOBILE

INSTALL

## Physical Characteristics

Inner conductor	Insulation	Material	FM-PE 1.4 mm (Ø) (5 pair)
			HD-PE 0.9 mm (Ø) (1 pair)
			HD-PE 0.9 mm (Ø) (2 cond.)
Overall shielding	Shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap
		Drain wire	BC 1 x 0.511 mm (Ø) (OFC)
Outer jacket	Material		PVC 9.5 mm (Ø)
	Colours		Black
	Braiding		AL-MG 16 x 12 x 0.12 mm (Ø)
Inner conductor	Material		BC 1 x 0.511 mm (Ø) (OFC) (5 pair)
			TC 7 x 0.16 mm (Ø) (OFC) (1 pair)
Type of cable			HDMI High Speed with Ethernet
Inner conductor	American Wire Gauge		24 AWG (5 pair)
			26 AWG (1 pair)
			26 AWG (2 cond.)

## Mechanical Characteristics

Temperature range	Fixed installation	- 40 °C till + 80 °C
	Flexible installation	- 15 °C till + 60 °C
Bending radius	Fixed installation	6 x outer diameter
	Flexible installation	8 x outer diameter

## Variants

- HDM24 10M - 10 meter
- HDM24 12M - 12 meter
- HDM24/1 - 100 m wooden reel
- HDM24/3 - 300 m wooden reel
- HDM24 - 1 meter