



## PT-561

HDMI & IR over Twisted Pair Transmitter

| HDMI | HDCP Compliant



The PT-561 and PT-562 are a twisted pair transmitter and receiver for HDMI and IR signals. The PT-561 converts an HDMI and IR signal to a twisted pair signal and the PT-562 converts the twisted pair signal back to an HDMI and IR signal

### FEATURES

**Max. Data Rate** - 4.95Gbps (1.65Gbps per graphic channel)

**HDTV Compatible**

**HDCP Compliant**

**Bidirectional IR Support** - IR is compatible with a Kramer transmitter and via a Kramer external remote IR receiver: C-A35M/IRR or C-A35M/IRE or C-A35M/2IRE

**Optional IR Emitter Cables** - C-A35/IRE-10 single emitter & C-A35/2IRE-10 dual emitter

**Optional External IR Receiver Cables** - C-A35M/IRR-3 and C-A35M/IRR-50

**System Range** - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 70m (230ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat723 cable

**Cable** - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground

**EDID PassThru** - Passes EDID signals between the source and display

**ON (Red) / Transmit (Green) Status LED**

**Power Connect™ System** - A single connection to the transmitter powers the receiver

**Ultra-Compact Pico TOOLS™** - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS:	1 HDMI connector
OUTPUTS:	2 CAT5 OUT on RJ-45 connectors
IR PORT:	Bidirectional on a 3.5mm mini jack
MAX. DATA RATE:	4.95Gbps (1.65Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
POWER CONSUMPTION:	5V DC, 440mA (transmitter and receiver together)
INCLUDED ACCESSORIES:	Power supply
OPTIONS:	RK-4PT 19" rack mount adapter
PRODUCT DIMENSION:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx
SHIPPING DIMENSION:	17.40cm x 12.00cm x 8.60cm (6.85" x 4.72" x 3.39" ) W, D, H
SHIPPING WEIGHT:	0.4kg (0.9lbs) approx

