

AWP06 Spring fit waterproof ceiling speaker 8 Ohm/100V

Highlights:

- IP65 Ingress protection
- Aluminum grill
- Multi-tapping 100V line transformer
- 4"dual cone driver
- Spring-clamp mounting mechanism
- plastic enclosure

The AWP06 is a waterproof ceiling speaker with a power of 6 Watt which meets the IP65 standard. It is designed to be used in a wide variation of in- and outdoor applications and damp locations and features a 4" loudspeaker. Due to its wide smooth frequency response and high efficiency, it ensures high-fidelity music reproduction and intelligible speech at very low distortion. It can be used in 8 Ohm low impedance systems or in 100V PA systems with power taps for 6 Watt, 3 Watt and 1.5 Watt.

Applications:

- Sport facilities
- Bathrooms
- Swimming pool areas
- Terraces
- Spas



Certification:



Impedance:



Voltage:



System specifications:

| Max. Power | | 10 W |
|----------------------------|-------------------|-----------------|
| RMS Power | | 6 W |
| Frequency | Response (± 3 dB) | 100 Hz - 15 kHz |
| Sound Pressure (Max. W/1m) | | 95 dB |
| Line Transformer Tappings | 1 | 6 W / 1666 Ω |
| | 2 | 3 W / 3333 Ω |
| | 3 | 1.5 W / 6666 Ω |
| Impedance | | 8 Ω |
| Ingress Protection rating | | IP65 |
| Drivers | | 4" |

Product Features:

| Dimensions | 130 x 140 mm (Ø x H) |
|-----------------------|----------------------|
| Built-in depth | 130 mm |
| Cut-out measurement | 125 mm (Ø) |
| Weight | 0.950 kg |
| Operating temperature | -20 °C ~ 60 °C |
| Construction | ABS |
| Colours | White (RAL9010) |

Shipping & Ordering:

| Packaging | Cardboard box |
|--------------------------|-----------------------|
| Shipping weight & volume | 1.088 kg - 0.0039 Cbm |