

QAI USB-A/D

Dante Dongle USB I/O



All Rights Reserved

Product Introduction

Thanks for choosing the QAI USB-A/D. It connects to your Dante network and supports 2x2 channels of bidirectional audio, allowing PC and mobile device to play out and receive audio with your Dante devices using a USB-A/C connection.

Features

- Plug and Play
- 24-bit audio support
- 2X2 audio channel
- Supports 802.3af PoE

Packing List

- 1 x DAN-D1
- 1 x Type-C to Type-C cable
- 1 x Type-C to Type-A cable
- 1 x User Manual

Note: Please contact your distributor immediately if any damage or defect in the components is found

Panel Description



- ① **RJ45:** Dante network communication port. Green steady light indicates system ready; yellow flashing light indicates link/data traffic. The green light will flash to identify the device when clicking the Dante Controller "Identify" button (an eye-shaped symbol) on the host computer.
- ② **USB-C:** 1 x USB-C, compliant USB 2.0 device

QAI USB-A/D

Dante Dongle USB I/O



All Rights Reserved

Product Introduction

Thanks for choosing the QAI USB-A/D. It connects to your Dante network and supports 2x2 channels of bidirectional audio, allowing PC and mobile device to play out and receive audio with your Dante devices using a USB-A/C connection.

Features

- Plug and Play
- 24-bit audio support
- 2X2 audio channel
- Supports 802.3af PoE

Packing List

- 1 x DAN-D1
- 1 x Type-C to Type-C cable
- 1 x Type-C to Type-A cable
- 1 x User Manual

Note: Please contact your distributor immediately if any damage or defect in the components is found

Panel Description



- ① **RJ45:** Dante network communication port. Green steady light indicates system ready; yellow flashing light indicates link/data traffic. The green light will flash to identify the device when clicking the Dante Controller "Identify" button (an eye-shaped symbol) on the host computer.
- ② **USB-C:** 1 x USB-C, compliant USB 2.0 device

Technical Specification

Dante	
Power	802.3af PoE
Sample Rate	48 kHz
Bit Depth	24
Model Name	USB 2X2
General	
Operation Temperature	-5 to +55°C
Storage Temperature	-25 to +70°C
Power Consumption	9W(Max)
Dimension (W*H*D)	115x 34 x 28 mm
Cable length	20cm
Net Weight	70g



Technical Specification

Dante	
Power	802.3af PoE
Sample Rate	48 kHz
Bit Depth	24
Model Name	USB 2X2
General	
Operation Temperature	-5 to +55°C
Storage Temperature	-25 to +70°C
Power Consumption	9W(Max)
Dimension (W*H*D)	115x 34 x 28 mm
Cable length	20cm
Net Weight	70g

