

AUDIO/VIDEO SIGNAL CABLE
RAV600



Composite

OUTER DIAMETER

5.8x12.6 mm

APPLICATIONS

Composite video + unbalanced stereo signal. Indoor, ideal for pre-cabling commercial and residential projects

<p>Inner Conductor</p> <p>TINNED COPPER</p>	<p>Shielding</p> <p>BARE COPPER BRAIDING</p>	<p>Compatible with</p> <p>NEUTRIK BNC CONNECTOR NBNC75BIJ9</p>	<p>75 Ω</p>
--	---	---	--------------------

GENERAL SPECS

Type of cable	Coaxial video cable & stereo audio cable
Outer jacket	Flexible PVC
Outer jacket colour	Black
Outer jacket dimensions	5,8 x 12,6 mm

VIDEO SECTION

Inner conductor	TC 1 x 0,8 mm
Inner conductor section	0,50 mm ²
Isolation	Foamed PE Ø 3,6 mm
Isolation colour	Yellow
Number of conductors	1
Shielding	BC 16 x 3 x 0,12 mm - Braiding
Shielding %	100%
Outer jacket	Flexible PVC
Outer jacket colour	Black
Outer jacket dimensions	Ø 5,8 mm
Impedance	75 Ohm
American Wire Gauge	20 AWG

AUDIO SECTION

Inner conductor	TC 7 x 0,2 mm
Inner conductor section	0,22 mm ²
Isolation	Foamed PE Ø 1,1 mm
Isolation colour	Red / White
Number of conductors	2
Shielding	BC 30 x 0,12 mm - Spiral
Shielding %	100%
Outer jacket	Flexible PVC
Outer jacket colour	Black
Outer jacket dimensions	Ø 3,4 mm
Inner jacket	Flexible PVC
Inner jacket colour	Black
Inner jacket dimensions	2 x Ø 5 mm
Impedance	110 Ohm

MECHANICAL SPECIFICATIONS

Temperature range	fixed installation	-40° C till +80° C
	flexible installation	-15° C till +60° C
Bending radius	fixed installation	6 x outer diameter
	flexible installation	8 x outer diameter

Available Lengths:
100 m plastic reel

