



RB-6

6-Channel Power Controller

| Ethernet - RJ-45



The RB-6 is a high-performance power supply that distributes power to up to six external units. Four power outlets have on/off push-button control and two power outlets have on/off switching as well as full voltage control

FEATURES

Active Output Control - All outputs On/Off control, 5 & 6 min/max with full voltage variability via rotary knobs

Power Output - 10A total, maximum 6A per output

Embedded Web Server Control - Turns On & Off all channels and adjusts voltage on 5 & 6, schedules outlet activity of each channel separately via Ethernet

Expandable - Cascades up to 8 units

Varied Control Options - Front panel buttons, IR remote control, RS-232, RS-485 & Ethernet

Indicators - Push button LEDs show active output, power and IR status LEDs

Worldwide Power Supply - 100-240V AC, US and EU models available

Standard 19" Rack Mount Size - 1U. Rack "ears" included



KRAMER

TECHNICAL SPECIFICATIONS

INPUT:	1 AC power input
OUTPUTS:	6 controllable AC power outputs
CONTROL:	Front panel buttons, IR remote control, RS-232 on a 9-pin D-sub connector, RS-485 on a 3-pin terminal block, Ethernet on an RJ-45 connector, embedded Web server
POWER CONSUMPTION:	100-240V AC, 50/60Hz, 30VA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Rack "ears", IR remote control, power cord
OPTIONS:	Remote IR receiver cable Kramer P/N 505-70434010-S
PRODUCT DIMENSION:	19" x 9.34 x 1U (43.6cm x 23.72cm 4.36cm) W, D, H
PRODUCT WEIGHT:	2.2kg (4.9lbs) approx
SHIPPING DIMENSION:	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
SHIPPING WEIGHT:	3.3kg (7.2lbs) approx

