

## **RTBUS-21xl**

Round Table Mount Multi-Connection Solution - Pneumatic Lid | VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



The RTBUS-21xl is an elegant furniture-mounted, modular, round connection bus featuring a pneumatic mechanism for pneumatic lifting and smooth closing of its lid. It is easily installed into a table or podium top and its interface enables you to connect any equipment to systems installed in a room via pass-through connectors for PC, stereo audio, HDMI, Ethernet and power.

NOTE: The power socket and power cord are purchased separately

## FEATURES

Inputs - 15-pin HD, 3.5mm, HDMI, Ethernet Cover - Pop-up pneumatic lid Cutout Size (Mount Dimension) - 111-114mm diameter



## TECHNICAL SPECIFICATIONS

Ports	1 HDMI: On a female HDMI connector
	1 VGA: On a 15-pin d-sub connector
	1 Audio: On a 3.5mm mini jack
	1 Ethernet: On an RJ-45 connector
PHYSICAL	Cutout Size: 111-114mm diameter
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F)
	Storage Temperature: -40° to +70°C (-40° to 158°F)
	Humidity: 10% to 90%, RHL non-condensing
Power	Power ratings vary according to the location and the power socket assembly installed on the tbus, as follows:
	Universal: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet
	USA: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Germany and EU: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Belgium and France: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Italy: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Australia: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Israel: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
	South Africa: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Switzerland: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
	England: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Brazil: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
	Fuse Rating: T 6.3A 250V
Accessories	Included: Mounting brackets
	Optional: TBUS AC power cord, power socket kits
Product Dimensions	15.70cm x 12.80cm x 15.35cm (6.18" x 5.04" x 6.04" ) W, D, H
Product Weight	0.0kg (0.0lbs) approx
Shipping Dimensions	36.50cm x 17.00cm x 17.00cm (14.37" x 6.69" x 6.69" ) W, D, H
Shipping Weight	1.3kg (2.9lbs) approx





CONFIGURATIONS	
RTBUS-21XL(B)	Round Table Mount Multi-Connection Solution — Pneumatic Lid — 110mm Cut-Out; Enclosure - Black Sand Blasted Anodized Aluminum Top
RTBUS-21XL(BC)	Round Table Mount Multi-Connection Solution — Pneumatic Lid — 110mm Cut-Out; Enclosure - Silver Sand Blasted Anodized Aluminum Top