

RTBUS-27xI

Round Table Connection Bus for Power Socket and Cable Pass-Throughs



RTBUS 27xl is an elegant furniture-mounted, round connection bus that houses a power socket and two cable pass-throughs. RTBUS 27xl features a pneumatic lid mechanism for lifting and smooth closing and is easily installed into a table or podium top.

NOTE: The power socket, power cord and cables are purchased separately

FEATURES

Customizable - Houses any of the following power sockets: USA, UK, Germany (the Europlug), Belgium-France, Switzerland, Italy, Australia, Brazil, Israel, South Africa or "Universal" for use anywhere

Hidden Cable Pass-Throughs - Enable closing the lid while keeping two cables hidden and protected under the table surface

Cutout Size (Mount Dimension) - 111-114mm (4.37in to 4.49in) diameter



TECHNICAL SPECIFICATIONS

Extended USB

Cutout Size 111-114mm (4.37in to 4.49in) diameter

Power

Power rating varies according to the location and the power socket assembly

(purchased separately) installed in the tbus, as follows:

Universal: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

USA: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Germany and EU: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Belgium and France: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Italy: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Australia: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Israel: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

South Africa: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

Switzerland: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

England: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

Brazil: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

Fuse Rating: T 6.3A 250V

Environmental Conditions

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

Regulatory Compliance (Standards Compliance) Safety: CE, UL

Environmental: RoHs, WEEE

COAX Included Clamp set

Optional TBUS AC Power Cord, power socket kits



CONFIGURATIONS

RTBUS-27XL(B)	Round Table Connection Bus — Sand-blasted Anodized Aluminum Top - Black
RTBUS-27XL(BC)	Round Table Connection Bus — Sand-blasted Anodized Aluminum Top - Silver