

RX115

Road Speaker

AUDAC

► Features

- High-fidelity, full range reproduction of music and speech
- Coverage pattern 90° x 75°
- Horizontal and vertical coverage
- Easy to handle
- Multi-angled enclosure
- Built-in rigging stand fitting
- Scratch-free EPDM coating

► Applications

- Road touring
- Stage monitor
- Clubs
- On stage
- Festivals



AUDAC's RX series are compact, full range loudspeakers especially designed for in- and outdoor applications.

The RX115 contains a special modified constant directivity horn with a 1.3" HF compression driver and a 15" high power low frequency loudspeaker. He is designed to work in a vertical as well as a horizontal position, with a coverage pattern of 90° x 75°.

Average power handling is 300W. On-axis frequency range is 62Hz to 18kHz. On-axis sensitivity (1W/1m) is 101 dB SPL and even reaches a maximum SPL of 126 dB.

For extra safety, there's a protection circuit placed inside to protect the 1.3" tweeter when overload occurs.

The very solid plywood enclosure with a scratch free, textured EPDM black painting makes the RX series excellent suitable for on the road use.

There's a built-in 35mm speaker stand adapter integrated in the bottom of the speaker, and the 12 rigging points located on every side of the speaker make it possible to let him fly.

Its multi-angled enclosure can be used arrayed, on a speaker stand, standing upright on the floor and also as a monitor.

At the back of the RX115, you will find two Neutrik Speakon NL4MP connectors. One of these two Speakon connectors can be used for linking a second RX115 to the first one.

Their very compact size and ergonomic grips make the RX115 easy to handle and transport.

Optional accessoires:

- CPB115R protective cover bag

► Specifications

SYSTEM SPECIFICATIONS	
Max power	600 W
RMS power	300 W
Impedance speaker	8 Ohm
Sound pressure 1W/1m	101 dB
Sound pressure Max W/1m	126 dB
Frequency response -3dB	62 Hz - 18 kHz
Frequency range -10dB	50 Hz - 20 kHz
Cross-over frequency	2 kHz
Crossover network	Passive built-in
Horizontal coverage	90°
Vertical coverage	75°
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	450 x 720 x 390 mm
Weight net	29 Kg
Drivers	HF 1,3" / MF 15"
Connectors	2 x Speakon NL4MP Neutrik
Construction	Plywood with textured EPDM black coating
Front finish	Perforated steel grill
Rigging flying points	12 x M10
Carry handles	One at the top
Rigging stand fitting	Built-in bottom 35 mm
Colour	Black
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	31 Kg - 0.126 Cbm
Accessories	CPB115R Protective cover bag

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products