


SPEAKER CABLE



★★★★★

SPEAKER CABLE

Applications
Indoor use
High-quality installations over long distances

RZ SERIES

- RZ07**
- RZ15**
- RZ25**
- RZ40**



The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible jacket of PVC. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are “all-round” loudspeaker cables suited for all kinds of applications on loudspeaker level.

GENERAL SPECIFICATIONS

| Cable model | RZ07 | RZ15 |
|-----------------------------------|---|---|
| Type of cable | Speaker cable | Speaker cable |
| Inner conductor | BC 10 x 7 x 0,12 mm | BC 20 x 7 x 0,12 mm |
| Inner conductor section | 0,7 mm ² | 1,5 mm ² |
| Number of conductors | 2 | 2 |
| Conductor twisting | No | No |
| Outer jacket | Flexible PVC | Flexible PVC |
| Outer jacket colour | Black with red molded line White with black molded line Grey with white molded line | Black with red molded line White with black molded line Grey with white molded line |
| Outer jacket dimensions | 2,6 x 5,2 mm | 3 x 6 mm |
| Lead resistance - 100 meter | 2,3 Ohm | 1,2 Ohm |
| Cable crosstalk - 100 meter | Min 74 dB | Min 74 dB |
| Cap. Lead to lead - meter @ 1 kHz | 76 pF | 95 pF |

| Cable model | RZ25 | RZ40 |
|-----------------------------------|---|---|
| Type of cable | Speaker cable | Speaker cable |
| Inner conductor | BC 30 x 7 x 0,12 mm | BC 50 x 7 x 0,12 mm |
| Inner conductor section | 2,5 mm ² | 4 mm ² |
| Number of conductors | 2 | 2 |
| Conductor twisting | No | No |
| Outer jacket | Flexible PVC | Flexible PVC |
| Outer jacket colour | Black with red molded line White with black molded line Grey with white molded line | Black with red molded line White with black molded line Grey with white molded line |
| Outer jacket dimensions | 4 x 8 mm | 5 x 10 mm |
| Lead resistance - 100 meter | 0,9 Ohm | 0,5 Ohm |
| Cable crosstalk - 100 meter | Min 74 dB | Min 74 dB |
| Cap. Lead to lead - meter @ 1 kHz | 118 pF | 128 pF |



Available Lengths:
100 m plastic reel
500 m Wooden reel



RZ07G



RZ07W

MECHANICAL SPECIFICATIONS

| | | |
|-------------------|-----------------------|---------------------|
| Temperature range | fixed installation | -40° C till +80° C |
| | flexible installation | -25° C till +70° C |
| Bending radius | fixed installation | 8 x outer diameter |
| | flexible installation | 10 x outer diameter |

