



## SDIA-IN4-F32

4-Channel SDI with Analog Audio Input Card

| Kramer Core



SDIA-IN4-F32 is a four-channel SDI input card with optional analog audio embedding for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The SDIA-IN4-F32 inputs four SDI with optional unbalanced stereo audio signals into the chassis and converts each SDI signal separately into HDMI format for routing within the matrix switcher

### FEATURES

- Max. Data Rate - 3Gbps
- Multi-Standard Operation - SDI, HD-SDI, 3G HD-SDI
- Stereo Audio Embedding



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS	4 unbalanced analog audio on 3.5mm mini jack connectors, 4 SDI, 75Ω on BNC connectors
TOTAL BANDWIDTH:	3Gbps
MAXIMUM RANGE:	300m (980ft) – SD, 200m (655ft) – HD 1080p, 90m (295ft) – 3G 1080p
3D PASS THROUGH:	Not supported
POWER CONSUMPTION:	11W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
Product Dimension	22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79" ) W, D, H
Product Weight	0.3kg (0.7lbs) approx
Shipping Dimension	25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17" ) W, D, H
Shipping Weight	0.5kg (1.0lbs) approx