



Halo Profile 200W

Product Code: SG HALOPWW2045

Profile projector zoom 20°/45° COB led 200W



Description

Halo profile led zoom is the result of a Sagitter project which can replace the most common incandescent profile projectors with a product featuring low consumption and the same luminous efficiency of the most common incandescent. The combination of a cutting edge power supply and a next generation 3200K white COB LED source, makes the projector suitable for stage of any size. This new profile projector is equipped with a variable zoom system able to modify its projection angle from 20° to 45°.

Technical Specifications

Light source

- 1X200W LED COB Warm White 3200K
- CR ≥85Ra
- LED lifespan > 50.000h
- LED refresh frequency: > 400Hz flicker free

Optic system

- Beam angle: zoom from 20° to 45°
- Luminous flux: 2950lux@5mt (20°)
- Luminous flux: 1550lux@5mt (45°)

Color system

- LED source COB warm white 3200K

Effects

- Linear dimmer 0 - 100%
- Strobe: electronic 1-20 flashes/s with adjustable speed

Control and programming

- 2 different DMX channels configurations: 1/2 channels
- Protocol USITT DMX 512

Structure and cabined

- Black aluminium housing
- LCD blue graphic display
- Fixing system with adjustable bracket
- Single handle in the rear side of the projector for easy transportation
- DMX control signal input and output XLR 3 poles
- IP rating: IP 20
- "low noise" controlled forced ventilation cooling system

Power supply

- Input voltage: AC~ 100-240V 50/60Hz
- Switching power supply unit
- Power consumption 250W
- IN/OUT power connection with powercon sockets
- Power supply cable 1,5 mt included
- Max 4 pcs linkable@240V

Weight and dimensions

- Net Weight: 10kg
- Dimension: 275x645x410 mm

Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. All trademarks are the property of their respective owners. PROEL accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. PROEL products are sold through authorized fullfillers and resellers only. This manual is copyrighter. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of PROEL - Via alla Ruenia 37/43 - CAP 64027 - Sant'Omero (TE) ITALY.

Sagitter is a brand of Proel Spa | Via alla Ruenia
37/43 64027 Sant'Omero (TE) ITALY
Tel. +39 0861 81241 | Fax. +39 0861 887862 |
www.sagitter.com

