



# IP Color 24C

*Product Code: SG IPLED24C*

IP 65 architectural led 24X8W RGBW/FC



## Description

---

IPLED is the new Sagitter series of IP65 projectors with LED source developed for various uses, common to all architectural and live lighting settings. Our main goal was colour equality of the "full colour" version IPLED projectors, achieved through the use of special high power RGBW/FC LED sources in the 4 models, two with 9 LEDs, one with 18 and one with 24. IPLED24C, the highest performing one of the line, has a powerful and diffused light beam suitable for large surfaces or locations, its light source consists of 24 8W RGBW/FC LEDs. Its die-cast aluminium mechanism makes it compact, sturdy and noiseless. The colour technology used offers a wide range of colours and thanks to the inclusion of the white LED source, it is possible to customise and balance the colour temperature, with a number of options already available and stored in the software. Furthermore, the IR remote control included makes it possible to individually control the product with no need for a control unit.

## Technical Specifications

---

### Light Source

- 24x8W led RGBW Full Color
- LED lifespan: > 50.000h
- LED refresh frequency: > 400Hz flicker-free

### Optic system

- Beam Angle: 25°

### Color system

- LED source RGBW Full color
- Infinite chromatic possibilities

### Effects

- Linear dimmer 0-100%
- Adjustable strobe effect
- Color macros selectable via DMX

### Control and programming

- 3 DMX configurations available: 3/6/7 channels
- Key lock password for display lock
- Protocol USITT DMX 512
- Master/Slave mode
- Auto mode
- Remote controller included

### Structure and cabinet

- Die cast aluminium housing
- Blue LCD graphic display
- Front tempered glass
- "Light up" positioning with adjustable angle
- IP rating: IP65
- DMX IN/OUT connectors IP65
- Convection cooling system without fans

**Power supply**

- Input Voltage: AC~100-240V, 50/60 Hz
- Switching power supply unit
- Power consumption: 200W
- IN/OUT power connection IP65

**Weight and Dimensions:**

- Net weight: 8,4 kg
- Dimensions: 288x130x325,6 mm