# **STAGE LEDS**

# **JUNIOR PROFILE**











SG JNRPROWW - PRODUCT CODE WARM WHITE VERSION SG JNRPROCW - PRODUCT CODE COLD WHITE VERSION SG JNRPRORGBW - PRODUCT CODE RGBW VERSION SG CASEJNRPRO - CASE (6X SG JNRPROWW)

# **LIGHT SOURCE**

- 1x30W Led Warm white 3200K
- LED lifespan: > 50.000h
- LED refresh frequency: > 400Hz anti-flicker

# **OPTIC SYSTEM**

- Beam Angle: 19° (included)
- Optional: 14° 26° 36°
- Luminous flux: 215 lux @5m (full on)

### **COLOR SYSTEM**

• LED source Warm white 3200K

#### **EFFECTS**

- Linear dimmer 0-100%
- Strobe: electronic 1-20 flashes/s with adjustable speed

# **CONTROL AND PROGRAMMING**

- 1 DMX channels configuration: 2 channels
- Protocol USITT DMX 512
- Auto mode: 1 programs can be selected from dip switch

# **STRUCTURE AND CABINET**

- High resistance black plastic and aluminium housing
- Mounting points: single bracket
- Gel filter frame included
- Gobo holder included
- Iris not included (sold separately)
- XLR 3-poles DMX IN/OUT connection
- IP rating: IP20

# **POWER SUPPLY**

- Input Voltage: AC~100-240V, 50/60 Hz
- Max power: 35W @ 230VAC
- Power supply cable 1mt included

# **WEIGHT AND DIMENSIONS**

- Net weight: 1,1 kg
- Dimensions: 160x265x205 mm

