

LED KIT 7

Product Code: SG LEDKITHP7

Led kit 4 projectors 7x10W led RGBW/FC





SDJ offers one of the most extensive selections when it comes to ready to use "plug & play" LED systems. The LED Kit series consists of a portable colour changing LED set, suitable for any user, whether experienced or not. A practical stand with 3 feet (supplied) supports the light bar, a pedal ensures easy control of the entire system and two handy bags (included) provide fast and secure transport. The second one of the series, can count on 7 high power 10W LED sources with 4 in 1 RGBW full colour technology; the high power and the addition of the white colour makes this kit unique for indoor entertainment. The light bar is also equipped with two adjustable side brackets which ensure fastening to structures or in "light up" positions on the ground. For the most demanding users, a control has been added that operates via the DMX signal, giving the possibility to fully customise all the functions and performance of the entire system.

Technical Specifications

Light source

- Kit 4 projectors 7x10W led RGBW Full Color
- LED lifes pan: >50.000h
- LED refresh frequency: >400Hz flicker free

Optic system

• Beam angle: 25°

Color system

- LED source 4 in 1 RGBW Full Color
- Infinite chromatic possibilities and colour temperature control

Effects

- Linear Dimmer 0-100%
- Electronic strobe: 1-20 flashes/s with adjustable speed
- 1 Auto mode can be recalled by DMX

Control and programming

- 5 DMX configurations available: 4/6/10/16/18 channels
- Each projector can be controlled independently
- Protocol USITT DMX 512
- Master / Slave mode
- Sound mode with adjustable mic sensitivity
- Automatic mode with 6 different programs selectable from the display or footswitch with independent adjustment of the speed
- Color mode with 9 different pre-programmed color macros + 1 adjustable macro
- Footswitch control included: Blackout, Sound, Auto, Freeze

Structure and cabinet

- Metal housing, black color
- Red LED display
- Mounting points: double adjustable bracket
- "Light up" positioning
- 3-poles XLR in/out connection

- IP rating: IP 20
- Stand max. H 2800 mm with bag for transport included
- Semi rigid bag for bar transport included

Power supply

- Input Voltage: AC~100-240V 50/60Hz
- Switching power supply unit
- Power consumption 300W
- Power IN/OUT connection with VDE socket
- Power supply cable 1,5 mt included

Weight and dimensions

Bar Net weight: 8,5 kgStand Net weight: 4,5 kg

• Bar dimensions: 1180x90x270 mm





