



---

# Pix.i 5 linear Beam

*Product Code: SG PIXI5WL*

Led bar 3W beam 5° Warm White pixel control



## Description

---

PIXI 5 White linear is a linear LED projector 12 pixels with a high power source of 3W Warm White 2800K. The optics, conceived with a beam projection angle of 5°, is equipped with an antireflection DC (dark cover) optical insulation system which ensures a precise and defined pixel effect, without any internal reflection interfering in the light effect. For an ultra easy-to-use experience, many macros have been included, which can be recalled via DMX with graphic pixel effects. A colour LCD display features an intuitive software interface, a black aluminium body with "fast lock" hardware for the connection of the modules ensures low weight and perfect alignment between the pixels.

## Technical Specifications

---

### Light source

- 12x3W CREE XPE led Warm White 2800K
- LED lifespan: >50.000h
- LED refresh frequency: >400Hz flicker free

### Optic system

- Beam angle: 5°
- Luminous flux: 3850lux @ 4m
- DC (dark cover) optical insulation system

### Color system

- LED source CREE Warm White 2800K

### Effects

- Linear Dimmer 0-100%
- Electronic strobe: 1-20 flashes/s with adjustable speed
- Color macros and pixel can be recalled by DMX

### Control and programming

- 4 DMX configurations available: 2/3/6/12 channels
- 3 selectable dimmer curve
- Pixel to pixel control
- Protocol USITT DMX 512
- Master / Slave mode
- Sound mode with adjustable mic sensitivity
- Static color mode with independent adjustment of strobe
- Automatic mode with independent adjustment of the speed

### Structure and cabinet

- Aluminium housing, black color
- LCD color display
- Mounting points: central bracket
- Specific hardware for connection between panels
- 3-poles XLR in/out connection
- IP rating: IP 20
- Fan cooling system without fans

### Power supply

- Input Voltage: AC~100-240V 50/60Hz
- Switching power supply unit
- Power consumption 40W
- Power IN/OUT connection with powerCON socket
- Power supply cable 1,5 mt included
- Max 20 pcs linkable @240V

**Weight and dimensions**

- Net weight: 2,5 kg
- Dimensions: 1000x55x142 mm

Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. All trademarks are the property of their respective owners. PROEL accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. PROEL products are sold through authorized fullfillers and resellers only. This manual is copyrighter. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of PROEL - Via alla Ruenia 37/43 - CAP 64027 - Sant'Omero (TE) ITALY.

Sagitter is a brand of Proel Spa | Via alla Ruenia  
37/43 64027 Sant'Omero (TE) ITALY  
Tel. +39 0861 81241 | Fax. +39 0861 887862 |  
[www.sagitter.com](http://www.sagitter.com)

