



Quariux

Product Code: SG QUARIUXRGBW

6x40W COB led bar RGBW IP67





Description

After an exhaustive period of research and comparisons with the help of the most famous architectural lighting and entertainment professionals, Sagitter's R&D team has conceived and designed Quariux, a LED-source bar with which it intends to enrich the Sagitter product range with the introduction of an innovative projector with many unique features. Quariux encompasses, with an Italian design, versatility and reliability combined with a very good weight, size and luminous efficiency ratio, such as to make this projector unique on the market.

Technical Specifications

Light Source

- 6x40W COB led
- LED lifespan: >50.000h
- LED refresh frequency: >500Hz flicker free

Optic system

- Beam angle: 12° (standard)
- SSZ: Solid State Zoom (da 12° a 90°) upon request
- Optional optic: 24° - 48° - 80° - 12°x90° (asymmetric)

Color system

- 4 in 1 led source RGBW Full Color (standard)
- Available possibilities: RGB – RGBL – WW – CW – VW
- Macro colors selectable via DMX
- Halogen and CMY Simulation

Effects

- Linear dimmer 16 bit 0 - 100%
- Electronic strobo 1-20 flash/s adjustable speed
- Overboost Blinder

Control and programming

- DMX configurations availables: 1/2/3/5/7/10 channels
- 4 dimmer curves selectable
- Protocol USITT DMX 512
- Master/Slave mode
- Presetted macro colors with speed regulation
- Static Color: static reproduction of one color
- Touch pad with led indicators
- Integrated wireless DMX

Structure

- Aluminium structure, available in black or customizable with other colors
- High tightness Lexan, resistant to cuts and perforations
- Fast coupling system
- Bracket for anchoring and ground support
- IP rating: IP 67
- Convection cooling system without fans
- Optional barndoor
- Operating temperature -20°C ~ 40°C

Power supply

- Input Voltage: ~88-264Vac 47/63Hz
- Universal switching power supply
- Double temperature control
- Power consumption: 250W
- IN/OUT power connection

Weight and dimensions

- Net weight: 3,7 kg
- Dimension:: 495x74x95 mm