



Slimpar FLC

Product Code: SG SLIMPARFLC

Slimpar strobe projector 224 smd led IRC (included)



Description

SLIMPAR rewrites lighting techniques. The line was completely designed to meet the needs of occasional users; the main feature of the projectors of this new line is ease of use, as all the functions of the projector have been fully simplified and optimised, e.g. by adding the IR control (included) that makes all operations easier, giving the possibility to launch "preset" programs or colours without using the DMX signal. Among the variety of available colours, the Slimpar line offers various "sizes" and "sources", in addition to the last generation DL (Dark Light) technology. Thanks to the use of these innovative high performance 6 in 1 RGBWAU LED sources it is possible to obtain ultraviolet light, now trendy in a great number of dance events, at the same time as maintaining all the many colour hues reproduced by the full colour RGBWA, RGBW, RGB sources. The body of all Slimpar projectors has been designed in ABS plastic, assuring the utmost sturdiness. The compact size assure various possible uses and pendant installation, thanks to handy anchor brackets and supported in "light up" position, directly exploiting the projector's exclusive design. As of today with this new model the product acquires the version with 224 white SMD 0.5W 6500K LEDs with a blinder effect full ON LED and flashing frequency close to 25 flashes per second at variable speed with concentric circle effect controllable both from DMX and automatically.

Technical Specifications

Light Source

- 224x0,5W led Edison 6500K
- LED lifespan: > 50.000h

Optic system

- Beam Angle: 120°

Color system

- LED source 224x0,5W led Edison 6500K

Effects

- Linear dimmer 0-100%
- Adjustable strobe effect
- Random strobe effect
- Circular sectors control

Control and programming

- 7 DMX configurations available: 1/2/4/7/8/9/11 channels
- Protocol USITT DMX 512
- Master/Slave mode
- Sound mode
- Auto mode
- IR remote control

Structure and cabinet

- ABS housing black color
- Red LED display
- Mounting points: double adjustable bracket
- "Light-up" positioning without brackets

- XLR 3-poles DMX IN/OUT connection
- IP rating: IP20
- Forced air fan cooling system

Power supply

- Input Voltage: AC~100-240V, 50/60 Hz
- Switching power supply unit
- Power consumption: 90W
- Power supply cable 1mt included

Weight and Dimensions:

- Net weight: 1,5 kg
- Dimensions: 257x130x240 mm

Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. All trademarks are the property of their respective owners. PROEL accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. PROEL products are sold through authorized fullfillers and resellers only. This manual is copyrighter. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of PROEL - Via alla Ruenia 37/43 - CAP 64027 - Sant'Omero (TE) ITALY.

Sagitter is a brand of Proel Spa | Via alla Ruenia
37/43 64027 Sant'Omero (TE) ITALY
Tel. +39 0861 81241 | Fax. +39 0861 887862 |
www.sagitter.com

