



NEW

SG SMTDOT - PRODUCT CODE

LIGHT SOURCE

- 1x40W RGBW led high brightness
- 12 RGB led for external ring
- LED lifespan: >50.000h

OPTIC SYSTEM

- Beam angle: 4°

COLOR SYSTEM

- LED source RGBW Full color
- Infinite chromatic possibilities

EFFECTS

- Ring color rainbow effect in both directions with adjustable speed
- Linear dimmer 0-100%
- Electronic high speed strobe from 1 to 20 flashes/s, with adjustable speed.
- Color macros selectable from DMX

CONTROL AND PROGRAMMING

- 2 different DMX channels configurations: 16/30 channels
- Protocol USITT DMX 512
- Master/Slave mode selectable
- Sound mode with adjustable sensitivity of microphone
- Reset via DMX

STRUCTURE AND CABINET

- Black metal Housing, and plastic materials with high resistance
- Red LED display
- Pan 540° / Tilt 210°
- Mounting points: 1 omega holder + safety ring
- 3-poles XLR in/out connection
- IP Rating: IP 20
- Forced air fan cooling system

POWER SUPPLY

- Input Voltage: AC~100-240V 50/60Hz
- Switching power supply unit
- Max Power: 60W @ 230VAC
- Power connection with VDE sockets
- Power supply cable 1,5 mt included

WEIGHT AND DIMENSIONS

- Net weight: 2,4 kg
- Dimensions: 160x160x230mm

