

# SL\*\*AP-PBMM0X 32"

## 500nit Digital Signage Monitor



### Key Feature

- FHD Resolution
- 500nits
- 7 × 24 Operation
- HDMI Input
- USB Media Playback
- Built-In Speaker
- Slim and Light Design
- Landscape & Portrait Installation support
- VESA Mounting Interface
- Anti-Glare Open cell

# Specification

<b>Model</b>	<b>SL32AP-PBMM0X</b>
<b>Display</b>	
<b>Screen Size (Diagonal)</b>	32 inch
<b>Native Resolution</b>	1920 (H) × 1080 (V)
<b>Aspect Ratio</b>	16 : 9
<b>Brightness</b>	500 cd/m <sup>2</sup>
<b>Contrast</b>	≥ 1200:1
<b>View Angle</b>	178°(H) / 178°(V)
<b>Display Color</b>	16.7M
<b>Response Time</b>	8ms
<b>Anti-Glare</b>	25%Haze
<b>Operation Time</b>	7 × 24H
<b>Life Time (Light Source)</b>	50,000 Hrs (Typ.)

<b>Interface</b>	
<b>Input</b>	HDMI × 2
<b>Output</b>	-
<b>External Control</b>	-
<b>Networks</b>	-
<b>Others</b>	USB × 1
<b>Built-In Speaker</b>	8W × 2 (8Ω)

<b>Power</b>	
<b>Power supply</b>	AC 100~240V 50/60Hz 1A
<b>Power consumption</b>	≤ 70W
<b>Standby</b>	0.5W

<b>Environment</b>	
<b>Operation Temperature</b>	0°C~40°C
<b>Operation Humidity</b>	20%~80% RH
<b>Storage Temperature</b>	-20°C~60°C
<b>Storage Humidity</b>	10%~80% RH

# Specification

<b>Model</b>	<b>SL32AP-PBMM0X</b>
<b>Physical</b>	
<b>Color</b>	Black
<b>On bezel ( off bezel ) (mm)</b>	16.2(L/R)/16.2(T)29.1 (B)
<b>Tempered Glass</b>	-
<b>Body Dimension w/o Stand (W×H×D, mm)</b>	735.9x216x487.7
<b>Set Weight w/o Stand</b>	3.5 Kg
<b>Package Dimension (W×H×D, mm)</b>	795x135x516
<b>Package Weight</b>	6 Kg
<b>VESA Mounting</b>	200 × 100

## Dimension Drawing

SL32AP-PBMM0X

Unit: mm

