

SM55E-SBM**55”****UHD Commercial Monitor**

Key Feature

- UHD ADSDS LCD Panel
- 800nits
- Built-In Speakers
- HDMI input port
- Full Metal Casing Design
- RS232 Control
- Structure Strengthened for Commercial Usage
- 7/24 Operation

Specification

Display

Model	SM55E-SBM
Screen Size (Diagonal)	55 inch
Native Resolution	3840 × 2160
Aspect Ratio	16: 9
Brightness	800 cd/m ²
Display Area	1209.6(H)x680.4(V)mm
Contrast	1200:1
View Angle	178°(H) / 178°(V)
Life Time (Light Source)	50,000 Hrs

Interface

A/V Input	USB x1, HDMI x1, DVI x1, VGA x1, CVBS x1, Audio x1, RS232 x1
A/V Output	Audio x1, RS232 x1
External Control	RS232 (RJ45)
Built-In Speaker	5W × 2 (8Ω)

Power

Power supply	AC 110~240V 50/60Hz
Power consumption (Rated)	165 W
Power consumption (Standby)	≤ 0.5 W

Environment

Operation temperature	0°C~40°C
Operation humidity	10%~80% RH
Storage Temperature	-10°C ~ 60°C (5°C ~ 40°C Recommended)

Specification

Physical

Body Dimension	1264.1(W) × 735.2(H) × 66.7 (D)mm
Set Weight	TBD
Package Dimension	TBD
Package Weight	TBD
Wall hanging screws	M8 x 4
Mounting Holes	700 × 400

Dimension Drawing

