

## T-REC5

Cable Retractor



T-REC5 is a cable retractor designed to be installed in meeting rooms, classroom or other AV site. T-REC54 extends common AV connector types and is easy to install and use

## **FEATURES**

**Provides Convenient and Easy-to-Use Connecting** - Pull the cable to extend up to 1.7m (5.6ft) from the installation site; the cable automatically locks in position to the desired length. When finished, slightly pull the cable again and it retracts into the housing

Improved Design - Including a round Coax flexible cable, quiet and smooth retraction Simple and Flexible Installation Options - Install Horizontally (recommended) or vertically under Kramer's New TBUS models or attach directly to the underside of a table

Available in 2 common configurations: - HDMI or USB-C FF - 4K@60 (4:4:4); 10Gbps; 100W power charging



## **TECHNICAL SPECIFICATIONS**

Ports 1 male Connector (fixed cable end): 35cm according to the retractor type

1 Male Connector (retractor cable end):

Environmental Conditions

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

Regulatory Compliance (Standards Compliance) Safety CE

Environmental ROHS, REACH

Enclosure Type: Plastic (ABS PC)

Color: Black

Fixed Cable Length: 35cm (13.8")

Retractable Cable Length: 170cm (67")

General Product Dimensions 25.5 x17.5 x6.1cm (10" x 6.9" x2.4) L,W,H

Product Weight 0.99Kg (2.19lds) approx

Shipping Dimensions 34 x 22 x 9.4cm (13.4" x 8.7" x 3.7") L,W,H

Shipping Weight 1.65Kg (3.64lbs) approx

Accessories Included: Four M5x10 screws, T-REC5-M-H (horizontal) mounting bracket



CONFIGURATI	C	١

T-REC5-HDMI	Table Retractor type 5 for HDMI cable 170cm length; 35cm tail
T-REC5-U32/FF	Table Retractor type 5 for USBC 3.2/FF - 4K@60 (4:4:4); 10Gbps; 100W power charging. Cable 170cm length; 35cm tail
T-REC5-M-H Mounting Bracket	Horizontal mounting bracket for Retractor type 5
T-REC5-M-V Mounting Bracket	Vertical mounting bracket for Retractor type 5