

TP-125xI

Computer Graphics Video, Stereo Audio & Bidirectional RS-232 over Twisted Pair Transmitter with EDID



The TP-125xl is an extended range twisted pair transmitter for computer graphics video, unbalanced stereo audio and bidirectional RS-232 control command signals. It converts the input signals to a twisted pair signal and transmits them over CAT 5 cable to a compatible receiver

FEATURES

Max. Resolution - WUXGA & 1080p

HDTV Compatible

System Range - More than 820ft (more than 250m)

EDID Capture - Copies and stores the EDID from a display device

Cable - We recommend the use of Kramer's BC-XTP high quality skew-free, unshielded twisted pair (UTP) cable. When using UTP cable, it is advisable to ensure that the cable is installed far away from electric cables, motors and so on, which are prone to create electrical interference

Bidirectional RS-232 Interface - Commands and data can flow in both directions via the RS-232 interface, allowing status requests and control of the destination unit



TECHNICAL SPECIFICATIONS

INPUTS: 1 computer graphics on a 15-pin HD connector, 1 unbalanced stereo audio on a

3.5mm mini jack, 1 bidirectional RS-232 on a 3-pin terminal block

OUTPUT: 1 twisted pair on an RJ-45 connector

RESOLUTION: Up to WUXGA and 1080p

RS-232 BAUD RATE: 9600 and 19200bps

RS-232 MODE: Full-duplex

AUDIO BANDWIDTH 20Hz to 20kHz @-3dB

(-3dB):

S/N RATIO: Video: 58dB unweighted, 68.3dB @5MHz weighted; Audio: <-84dB

TOTAL GAIN: Audio: Analog/analog: 0dB; Analog/SPDIF: -12dBFS

COUPLING: AC

THD+N: Audio: <0.02%

PRODUCT 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

DIMENSION:

POWER

SHIPPING WEIGHT: 0.5kg (1.0lbs) approx

CONSUMPTION:

RANGE: Up to 250m (820ft)

0° to +40°C (32° to 104°F)

OPERATING TEMPERATURE:

STORAGE -40° to $+70^{\circ}$ C (-40° to 158° F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

12V DC, 450mA

INCLUDED

ACCESSORIES:

Power supply

OPTIONS: RK-3T 19" rack mount adapter

