



TP-45EDID

Component Video or Computer Graphics
Video with Audio over Twisted Pair
Transmitter with EDID

| VGA/UXGA - 15-pin HD



The TP-45EDID is a high-performance twisted pair transmitter for computer graphics or component video and unbalanced stereo audio signals. It converts the input signals to a twisted pair signal that it transmits to a compatible receiver

FEATURES

HDTV Compatible

Max. Resolution - WUGXA (15-pin HD) & 1080p (component)

Independently Selectable Video and Audio Sources - Computer graphics or component video, analog or digital audio

System Range - Up to 100m (330ft)

Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other

Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5

EDID Capture - Copies and stores the EDID from a display device

Controls - Front panel input selector and EDID capture buttons, remote input selector terminal block

Indicators - Input selection and EDID status LEDs

Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

VIDEO INPUTS:	1 component video, 1Vpp/75Ω(Y,Pb,Pr) on 3 RCA connectors; 1 XGA on a 15-pin HD connector
AUDIO INPUTS:	1 unbalanced stereo audio, 0dBu/50kΩ, on a 3.5mm jack; 1 S/PDIF audio on an RCA connector
POWER CONSUMPTION:	12V DC, 920mA max. (TP-46N, TP-45EDID pair when powered from the TP-45EDID via power connect, CAT 5, 60m); TP-45EDID self current: 110mA
OUTPUT:	1 twisted pair on an RJ-45 connector (video/audio)
MAX. INPUT LEVEL:	XGA: 1.7Vpp on 75Ω, DC coupling; Y,Pb,Pr: 1.05Vpp on 75Ω, AC coupling
RETURN LOSS:	-18dB
VIDEO RESOLUTION:	Up to UXGA, 1080p
S/N RATIO:	69dB RMS @5MHz
K-FACTOR:	0.2%
ISOLATION (CROSSTALK):	-43dB @5MHz
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx
AUDIO BANDWIDTH:	20Hz to 20kHz
TND+NOISE:	0.33% @1kHz
SAMPLE RATE CONVERSION:	48kHz
RESOLUTION CONVERSION:	24 bits
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Power supply

