

TP-578H

HDMI Receiver with RS-232, IR & Stereo Audio over PoC Long-Reach DGKat

| HDMI | HDCP Compliant | DGKat



The TP-578H is a DGKat twisted pair receiver for HDMI, IR and control signals. The unit receives a DGKat twisted pair signal from a compatible Kramer DGKat transmitter (such as a TP-577VH) and decodes it into HDMI, balanced and unbalanced stereo, S/PDIF digital audio, IR and RS-232 signals

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel)

HDTV Compatible

HDCP Compliant

HDMI Support - x.v. Color™, 3D and 7.1 multi-channel audio

DGKat™ Signal Integration - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

K-Link™ - Kramer's technology for controlling the device from a remote controller and passing data to external devices

PowerConnectPlus - A single connection to the transmitter or the receiver powers both units. The higher voltage PowerConnectPlus also powers regular PowerConnect devices via auto-negotiation

Configurable External Control

Analog and Digital Audio De-Embedding

Indicators - LEDs for mirroring

System Range - Up to 90m (295ft) at 1080i @60hz or up to 70m (230ft) at 1080p @ 60hz when using Kramer DGKat cables. Note: Transmission range depends on the signal resolution, graphics card and display used. If using third–party shielded CAT cables, both ends of the shield must be soldered to the connectors for the products to function properly

Controls - IR data transceiver



TECHNICAL SPECIFICATIONS

INPUTS: DGKat twisted pair on an RJ-45 connector

OUTPUT: HDMI, unbalanced stereo audio on a 3.5mm mini jack, balanced stereo audio on a

terminal block, S/PDIF on an RCA connector

POWER 12V DC, 200mA CONSUMPTION:

INCLUDED

Power supply ACCESSORIES:

Product Dimensions 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

Shipping Weight 0.5kg (1.0lbs) approx



