



kramer

TP-780T

4K60 4:2:0 HDMI HDCP 2.2 PoE Transmitter
with RS-232 & IR over Long-Reach
HDBaseT

| HDMI | HDBaseT | 4K/60 UHD (4:2:0)
| HDCP 2.2 Compatible



TP-780T is a high-performance, long-reach HDBaseT transmitter for 4K60Hz (4:2:0) HDMI, RS-232 and IR signals over twisted pair. TP-780T converts all input signals into the transmitted HDBaseT signal. It extends video signals to up to 40m (130ft) over CAT copper cables at up to 4K@60Hz (4:2:0) 24bpp video resolution and provides even further reach for lower HD video resolutions

FEATURES

High Performance Standard Extender - Professional HDBaseT extender for providing long-reach signals over twisted-pair copper infrastructures. TP-780T is a standard extender that can be connected to any market-available HDBaseT-compliant extension product. For optimum extension reach and performance, use recommended Kramer cables

HDMI Signal Extension - HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0. EDID and CEC signals are passed through from the source to the display

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling, processing and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems

Multi-channel Audio Extension - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

Bidirectional RS-232 Extension - Serial interface data flows in both directions, allowing data transmission and device control

Bidirectional Infrared Extension - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line

Cost-effective Maintenance - Status LED indicators for HDMI and HDBT ports facilitate easy local maintenance and troubleshooting. Local firmware upgrade via RS-232 connection and the K-Upload tool ensures lasting field-proven deployment

Easy and Elegant Installation - Single cable connectivity for both HDBaseT signals and power. Compact MegaTOOLS™ fan-less enclosure for dropped-ceiling mounting, or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter



kramer

TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| INPUTS: | 1 HDMI on an HDMI connector |
| OUTPUTS: | 1 HDBT on an RJ-45 female connector |
| PORTS: | 1 IR on a 3.5mm mini jack for IR link extension, 1 RS-232 on a 9-pin D-sub connector for serial link extension and device firmware upgrade |
| EXTENSION LINE: | HDBaseT 1.0 compliant; Up to 40m (130ft) at 4K @60Hz (4:2:0); up to 70m (230ft) at full HD (1080p @60Hz 36bpp); Note: When using Kramer HDBaseT cables |
| VIDEO: | Up to 10.2Gbps bandwidth (3.4Gbps per graphic channel) Up to 4K UHD @60Hz (4:2:0) 24bpp resolution HDCP 2.2 signal compliance Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0 |
| EXTENDED RS-232: | 300 to 115200 baud rate |
| CONTROL RS-232: | 115200 baud rate |
| POWER SOURCE: | 48V DC, 1.36A |
| POWER CONSUMPTION: | 48V DC, 240mA |
| ENCLOSURE: | Mega Tools size, aluminum type |
| COOLING: | Convection ventilation |
| OPERATING TEMPERATURE: | 0° to 40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power supply |
| Product Dimensions | 19.00cm x 11.60cm x 2.70cm (7.48" x 4.57" x 1.06") W, D, H |
| Product Weight | 0.4kg (1.0lbs) approx |
| Shipping Dimensions | 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H |
| Shipping Weight | 1.0kg (2.2lbs) approx |



