



# KRAMER

## TR-2A

Balanced Stereo Audio Isolation Transformer

---



The TR-2A is a high-performance isolation transformer for balanced stereo audio signals. It completely isolates devices to eliminate hum, ground loops, and DC offsets that can degrade audio quality.

## FEATURES

---

**S/N Ratio** - -83dB @+4dBu, 1kHz

**External Input & Output Ground Terminals**

**Grounding Options** - DIP-switch selectable

**Passive** - No power required

**Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3TR rack adapter



## TECHNICAL SPECIFICATIONS

---

INPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block
OUTPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block
MAX. OUTPUT LEVEL:	+26dBu
BANDWIDTH (-3dB):	20Hz to 20kHz
S/N RATIO:	-83dBu @+4dBu/1000Hz
CONTROLS:	DIP-switches to connect to chassis
COUPLING:	Transformer
AUDIO THD + NOISE:	0.025% @+4dBu/1000Hz
INCLUDED ACCESSORIES:	Mounting brackets
OPTIONS:	RK-3TR 19" rack adapter
PRODUCT DIMENSION:	12.12cm x 7.23cm x 3.07cm (4.77" x 2.85" x 1.21" ) W, D, H
PRODUCT WEIGHT:	0.3kg (0.6lbs) approx
SHIPPING DIMENSION:	23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H
SHIPPING WEIGHT:	0.5kg (1.2lbs) approx

