



Digital Conference System Extension Controller

TS-0605M



Feature

- *Smart touch buttons, easy operation. With recording, playback control, mode, quantity switching and volume shortcut key.
- *With 4 meeting modes: FFIO, NORMAL, FREE, APPLY.
- *Spokesman quantity limitation: option for 1, 2, 4, 6. Chairman is not limited.
- *Support Max 30 pieces microphone units.
- *Hand in hand cable connection way, easy for installation and maintain.
- *Adopt digital equalization module and noise reduction processing module for audio processing, to ensure clear and good sound quality. With 1 channel audio input and 1 channel audio output.
- *With 1 group original audio channel output, connect with amplifier.
- *With 1 group recording channel output, connect with external recording device.
- *Built-in recording function and SD interface, can record meeting conversation.
- *Can connect external mic, gain is adjustable.
- *With 48V Phantom power can be controlled, connect with external mic, gain is adjustable.
- *Support 24V DC power supply, for the controller and mic units.
- *Control unit shell adopt metallic material, both shell and cables has the connection with ground line, to ensure the function of antistatic 6000V.
- *Delicate desktop design, easy for operation.
- *With 3.5mm headphone jack, monitoring meeting conversation.

| | |
|---------------------|---|
| Model | TS-0605M |
| Microphone Quantity | ≤30 |
| Frequency Response | 30Hz ~ 20KHz |
| SNR | >75 dB(A) |
| Dynamic Range | >80 dB |
| Crosstalk | >80 dB |
| THD | <0.05% |
| Power Supply | 24V DC |
| Audio Input | LINE IN : 350mV Balance |
| Audio Output | LINE OUT 1: 1V Balance |
| Output Load | >1KΩ |
| Static Consumption | 10W |
| Output Consumption | 70W |
| Connector | 8 core aviation plug |
| Standards | IEC60914 |
| Working Temperature | -10°C~+60°C |
| Working Humidity | 20%~80% relative humidity, without condensation |
| Color | Black |
| Dimension(mm) | 210(L)×132(W)×50(H) |
| Weight | 1.65kg |