
# TSD-ZDC



# 4 x 4 Impedance Divider/Combiner





TSD-ZDC

#### **Features**

- 1 In x 3 Out, 2 In x 2 Out, 150Ω Input/Outputs
- 1 In x 3 Out, 2 In x 2 Out, 10K Input/Outputs
- Split or Combine Any Signal
- RF Filtering on All Inputs
- Individual Input Grounds
- Removable I/O Connectors
- No External Power Required
- Compact Chassis Design

#### **Audio Applications**

- Combine up to 3 Microphones to One Output
- Divide a Signal Microphone Signal to Three Mic Outputs
- Combine Stereo Signals Into a Mono Signal
- Divide a Mono Line Level Signal to a Simulated Stereo Signal
- Add a Zone

## **Atlas Time Saving Devices**

New Atlas Sound Time Saving Devices are designed to solve some of the common audio system problems in the easiest and in the most efficient and cost-effective way. Utilizing the highest quality components and inspired by real world installation issues, the Atlas Sound TSDs include mixers, amplifiers, preamps, and other distribution and control devices to simplify your connections, provide specific application needs, and add flexibility in expansion and changes that prevent expensive system overhauls.

The Time Saving Devices are loaded with features making it versatile and user friendly. The TSD design mandate was to make the installation quick and reliable, saving you valuable time and money. Each model is housed in a compact 1.5" x 4" x 2.75" footprint that allows for placement almost anywhere. Common features include removable individual I/O connectors for quick and precise wiring, separate ground terminals for all I/Os assuring secured connections, and removable level controls that can be replaced with a tamper-proof security cover.

#### Description

The Atlas Sound TSD-ZDC is a universal impedance divider/combiner for passively summing or splitting of mic or line level signals.

Features include four balanced 10K and four balanced 150 $\Omega$  inputs/outputs that may be passively split or combined in any arrangement.

Typical applications include:

- \*Passive summation of multiple 150 $\Omega$  mics or stereo 10K sources
- \*Passive splitting of  $150\Omega$  or 10K input sources to multiple outputs

To ease contractor use and installation the TSD-ZDC includes individual ground connectors for each input/output. The unit's compact footprint allows easy standalone mounting or an optional rack mount adapter may be used to facilitate up to (4) TSD devices.

#### Installation

- Government Buildings
- Medical Facilities
- Office Environments
- Churches
- Restaurants
- Schools
- Industrial Facilities
- House of Worship



### **Specifications**

**Description** Audio Impedance Combiner/Divider

Chassis ColorBlackChassis MaterialAluminum

Inputs/Outputs

150 $\Omega$  Network Oty4, Passive Balanced Networks, Any Channel Can Be Used for Input or Output 10K $\Omega$  Network Oty4, Passive Balanced Networks, Any Channel Can Be Used for Input or Output

Connection Removable 3 Position Captive Screw 3.5mm Spacing

**Electrical** 

Isolation Passive Filters RF

Frequency Response 20Hz - 20kHz (-1dB)

Mounting

Velcro Industrial Grade, Included

TSD-RMK Optional 1 RU Rack Mount Panel (Supports 4 TSD Units)

**Power Requirements** 

None Passive

**Dimensions** H 1.5" (39mm) x W 4" (101mm) x D 2.75" (70mm)

Weight 6oz, .165kg



