



kramer

UHDS-OUT2-F16

2-Channel 4K HDMI Scaler-Switcher Output Card

| HDMI | HDCP Compliant | Kramer Core



UHDS-OUT2-F16 is a two-channel HDMI scaler card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The card scales each output signal separately to a set resolution, aspect ratio and color depth according to the native requirements of the screen or to a user setting. The scaling ensures ultra-fast switching by eliminating dependency on the display's scaling capabilities while keeping a constant output signal. In addition, it features immediate (between frame) cut switching between both ports on the same card for live-event switching/scaling

FEATURES

- Max. Data Rate - 8.91Gbps (2.97Gbps per graphic channel)
- Max. Scaled Output Resolution - 4K@30Hz (4:4:4)
- Max. Input Resolution - 4K@30Hz (4:4:4)
- HDMI, HDCP, EDID Support
- Immediate Frame-to-Frame Switching Support



kramer

TECHNICAL SPECIFICATIONS

| | |
|--------------------------|---|
| Outputs | 2 HDMI On female HDMI connectors |
| Video | Max. Data Rate 8.91Gbps (2.97Gbps per graphic channel) Max. Scaled Output Resolution 4K@30Hz (4:4:4) Max. Input Resolution 4K@30Hz (4:4:4) Switching Time Between Inputs Less than 300ms (seamless) Video Latency Less than 3 frames Output Resolutions 1920x1080p@60Hz, 1920x1080p@50Hz, 1280x720p@60Hz, 1280x720p@50Hz, 720x480p@60Hz, 720x586p@50Hz, 1920x1080p@25Hz, 1920x1080p@30Hz, 3840x2160@30Hz, 3840x2160@25Hz Standards Compliance HDCP 1.4, HDMI 1.3a, HDTV compatible 3D Pass-through Not supported |
| Extension Line | Max. Range 15m (49ft) – 1080p 12 bit (deep color) |
| Power | Consumption 22W |
| Environmental Conditions | Operating Temperature 0° to +40°C (32° to 104°F) Storage Temperature -40° to +70°C (-40° to 158°F) Humidity 10% to 90%, RHL non-condensing |
| STANDARDS COMPLIANCE | Safety CE Environmental Complies with appropriate requirements of RoHs and WEEE |
| Product Dimensions | 19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79") W, D, H |
| Product Weight | 0.2kg (0.4lbs) approx |
| Shipping Dimensions | 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H |
| Shipping Weight | 0.3kg (0.7lbs) approx |

