

UTBUS-1xl

Under-the-Table Modular Multi-Connection Solution Enclosure

| VGA/UXGA - 15-pin HD



The UTBUS-1xl is the enclosure of a new modular system. A complete UTBUS system requires the enclosure, a power socket, inserts and a power cord.

NOTE: The UTBUS enclosure, power socket, power cord & inserts are purchased separately

FEATURES

Power Sockets - 8 different "TS" single power socket options are available to accommodate the power requirements worldwide

Power Cord - 8 different "C-AC" single power cords for each power socket Insert Slots - 6

Installation Requirement - Requires 29.0cm x 13.7cm (11.4in x 5.4in) of free space beneath the table Weight - 0.6kg (1.32lbs) approx



TECHNICAL SPECIFICATIONS

POWER SOURCE (AC power limits):	Universal: 100-240V AC, 50/60Hz, 5A; USA: 100-240V AC, 50/60Hz, 5A; UK: 100-240V AC, 50/60Hz, 5A; Germany and EU: 100-240V AC, 50/60Hz, 5A; Belgium and France: 100-240V AC, 50/60Hz, 5A; South Africa: 100-240V AC, 50/60Hz, 5A; Australia: 100-240V AC, 50/60Hz, 5A
FUSE RATING:	T 6.3A 250V
INCLUDED ACCESSORIES:	Self locking ties, wood screws
OPTIONS:	Passive wall plate inserts and interfaces, power cord
Product Dimensions	27.50cm x 10.20cm x 6.50cm (10.83" x 4.02" x 2.56") W, D, H
Product Weight	2.0kg (4.4lbs) approx
C C	2.0kg (4.4lbs) approx 34.00cm x 24.80cm x 9.70cm (13.39" x 9.76" x 3.82") W, D, H