

## VA-8xI

8-Channel Balanced Stereo Volume Controller



The VA-8xl is a high-performance 8 channel-balanced stereo input volume controller for balanced audio signals on terminal block connectors. The volume of each L & R stereo channel can be adjusted independently of the other stereo channel

## **FEATURES**

Input - 8 balanced stereo

Output - 8 balanced stereo

S/N Ratio - >90dB

Volume - -95dB to +31dB in 0.5dB steps; L& R channels may be controlled separately or together

Control - Front panel, RS-232 and RS-485

Worldwide Power Supply - 100-240V AC

Standard 19" Rack Mount Size - 1U



## TECHNICAL SPECIFICATIONS

INPUT: 8 balanced stereo audio  $+4dBu/30k\Omega$  on detachable terminal blocks

OUTPUT: 8 balanced stereo audio  $+4dBu/50\Omega$  on detachable terminal blocks

GAIN: -95dB to +31dB

MAX. OUTPUT

LEVEL:

>20dBu balanced (THD+N <0.01)

BANDWIDTH ( - 3dB): 20Hz to 40kHz

NOISE FLOOR: <90dB (gain 0dB)

THD + NOISE: 0.006% @4dBu 1kHz

CONTROL: Front pushbuttons, RS-232, and RS-485

INDICATORS: Gain in dB for left and right channels

POWER 100-240V, 13VA

CONSUMPTION:

INCLUDED Power cord, null-modem adapter, Windows®-based Kramer control software

ACCESSORIES:

PRODUCT 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

DIMENSION:

PRODUCT WEIGHT: 2.7kg (6.0lbs) approx

SHIPPING 55.00cm x 27.60cm x

DIMENSION:

55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21" ) W, D, H

SHIPPING WEIGHT: 3.5kg (7.8lbs) approx

