



## VGA-IN2-F16

2-Channel VGA Input Card

| Kramer Core



VGA-IN2-F16 is a two-channel VGA input card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGA-IN2-F16 inputs two VGA signals into the chassis

### FEATURES

- Max bandwidth - 450MHz
- Auto or User-Defined Resolution Detection & Phase Mode
- Adjustable Brightness & Contrast



# KRAMER

## TECHNICAL SPECIFICATIONS

---

PORTS:	2 VGA on 15-pin HD connectors
BANDWIDTH:	450MHz
MAXIMUM RANGE:	10m (32ft)
POWER CONSUMPTION:	5.5W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
Product Dimension	19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79" ) W, D, H
Product Weight	0.1kg (0.3lbs) approx
Shipping Dimension	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05" ) W, D, H
Shipping Weight	0.3kg (0.6lbs) approx