

VGA-OUT2-F16

2-Channel VGA Output Card

| Kramer Core



VGA-OUT2-F16 is a two-channel VGA output card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGA-OUT2-F16 outputs two VGA signals from the chassis

FEATURES

Max bandwidth - 450MHz Auto or User-Defined Resolution Detection & Phase Mode Adjustable Brightness & Contrast



TECHNICAL SPECIFICATIONS

PORTS: 2 VGA on 15-pin HD connectors

BANDWIDTH: 450MHz

MAXIMUM RANGE: 10m (32ft)

POWER

CONSUMPTION:

OPERATING 0° to +40°C (32° to 104°F)

CE

4W

TEMPERATURE:

STORAGE –40 TEMPERATURE:

-40° to +70°C (-40° to 158°F)

HUMIDITY: 10% to 90%, RHL non-condensing

SAFETY

REGULATORY COMPLIANCE:

Complies with appropriate requirements of RoHs and WEEE

ENVIRONMENTAL REGULATORY COMPLIANCE:

OOMI LIMIOL.

Product Dimensions $19.00 \text{cm} \ x \ 13.00 \text{cm} \ x \ 2.00 \text{cm} \ (7.48 \text{"} \ x \ 5.12 \text{"} \ x \ 0.79 \text{"}) \ W, \ D, \ H$

Product Weight 0.2kg (0.3lbs) approx

Shipping Dimensions 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

Shipping Weight 0.4kg (0.8lbs) approx