

VGAA-IN4-F32

4-Channel VGA with Analog Audio Input Card

| Kramer Core



VGAA-IN4-F32 is a four-channel VGA with analog audio input card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. VGAA-IN4-F32 inputs four VGA with analog audio signals into the chassis. Audio is accessed by connecting the supplied Kramer VGA with audio cables to each VGA port

FEATURES

Max. Bandwidth - 450MHz HDTV Compatible Analog Audio Over Breakaway Connector



TECHNICAL SPECIFICATIONS

INPUTS 4 VGA on 15-pin HD connectors, 4 unbalanced analog audio on 3.5mm mini jack

connectors (accessible via C GF/GMAF-30 cables)

BANDWIDTH: 450MHz

MAXIMUM RANGE: 10m (32ft)

Power Consumption 20W

OPERATING TEMPERATURE:

0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE: -40° to +70°C (-40° to 158°F)

HUMIDITY: 10% to 90%, RHL non-condensing

SAFETY REGULATORY COMPLIANCE: CE

ENVIRONMENTAL REGULATORY COMPLIANCE: Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES:

4 C-GF/GMAF-30 cables

Product Dimension

22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H

Product Weight

0.3kg (0.7lbs) approx

Shipping Dimension

35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H

Shipping Weight

0.5kg (1.2lbs) approx