

VGAA-OUT4-F32

4-Channel VGA with Analog Audio Output Card

| Kramer Core



VGAA-OUT4-F32 is a four-channel VGA with analog audio output card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The VGAA-OUT4-F32 outputs four VGA with analog audio signals from the chassis. Audio output is accessed by connecting the supplied Kramer VGA with audio cables to each VGA port

FEATURES

Max. Bandwidth - 450MHz HDTV Compatible Analog Audio Over Breakaway Connector



TECHNICAL SPECIFICATIONS

OUTPUTS 4 VGA on 15-pin HD connectors, 4 unbalanced analog audio on 3.5mm mini jack

connectors (accessible via C GF/GMAF-30 cables)

BANDWIDTH: 450MHz

MAXIMUM RANGE: 10m (32ft)

OPERATING (TEMPERATURE:

0° to +40°C (32° to 104°F)

STORAGE -40° to $+70^{\circ}$ C (-40° to 158° F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

Power Consumption 10W

SAFETY

CE

REGULATORY COMPLIANCE:

ENVIRONMENTAL REGULATORY COMPLIANCE:

Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES:

4 C-GF/GMAF-30 cables