


VIA GO

Wireless Presentation Solution

| HDMI | Ethernet - RJ-45





FEATURES

Wireless Device Connectivity - No dongle needed

60fps Streaming Multimedia - Share HD wireless video streaming (using the VIA app Multimedia feature). Supports up to 6Mbps video bit rate when using the builtin WiFi module in Access Point mode

Easy to Use - Simple and intuitive user interface

Display Participants - Up to two participant screens can be displayed simultaneously on main screen Graphic Output Formats - Outputs to either an HDMI or Mini DisplayPort display. Note: Does not support graphic output to both the HDMI and Mini Display Port simultaneously

iOS and Android Mirroring

Seamless Integration with VIA Site Management (VSM) Software & the VIA Pad

Digital Signage - Enables you to display dynamic content and information on the main display when there is no meeting in progress. Use a predefined template or create your own display configuration with up to three frames of content that appear simultaneously. Schedule campaigns (content configurations) to run automatically at specific dates and times.

NOTE: All VIA devices purchased after June 1, 2019 include the Digital Signage feature. If your device was purchased before that date, the feature can be purchased separately, see the ACCESSORIES & RELATED PRODUCTS tab

Wi-Fi Band Support - 2.4GHz (Access Point mode), 2.4GHz/5GHz (Client mode)

Warranty - 3-years on hardware



TECHNICAL SPECIFICATIONS

I/O: 4 USB 3.0, 1 LAN on an RJ45 connector

GRAPHIC OUTPUTS: 1 HDMI, 1 mini DisplayPort, support up to 1080p60 (using the VIA app Multimedia

feature) / WUXGA resolution.

Note: Does not support graphic output to both the HDMI and Mini Display Port

simultaneously

AUDIO OUTPUT: 3.5mm mini jack for HP/speakers

PROCESSOR: Intel® Braswell CPU, Dual Core 1.04GHz

MAIN MEMORY: 2GB, highspeed

STORAGE: eMMC, 32GB

LAN: Gigabit LAN

WIRELESS

COMMUNICATION:

Intel dualband wireless 802.11ac model 3168NGW

AUDIO: Analog or embedded HDMI

POWER SUPPLY: 45W power adapter (19V/2.37A)

INPUT VOLTAGE: 100V~220V AC, 50/60Hz, auto sensing

INCLUDED

ACCESSORIES:

Power cord, VESA mounting bracket

Product Dimensions 10.80cm x 11.50cm x 3.30cm (4.25" x 4.53" x 1.30") W, D, H

Product Weight 0.4kg (0.9lbs) approx

Shipping Dimensions 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

Shipping Weight 0.9kg (2.0lbs) approx

