



## VM-22HD

Dual-Mode 1:2 HD-SDI Distribution Amplifier

---



The VM-22HD is a high-performance distribution amplifier for HD-SDI and dual link HD-SDI signals. The unit can be configured as a dual 1:2 distribution amplifier, or as one 1:2 dual-link distribution amplifier

### FEATURES

---

**Max. Data Rate** - 1.485Gbps

**HDTV Compatible**

**Multi-Standard Operation** - SDI (SMPTE 259M and SMPTE 344M), HD-SDI (SMPTE 292M) & dual link (SMPTE 372M)

**Dual-Mode Operation** - Configure as two 1:2 or one dual link 1:2 DA

**Kramer Equalization & re-Klocking™ Technology** - Rebuilds the digital signal to travel longer distances

**HD-SDI & SDI Input Indication LEDs**

**Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS:	2 SMPTE-259M, 344M, 292M, 372M serial video, 75Ω on a BNC connector
OUTPUTS:	4 equalized and reclocked SMPTE-259M, 344M, 292M, 372M outputs, 75Ω on BNC connectors
MAX. OUTPUT LEVEL:	800mVpp/75Ω
MAX. BAUD RATE:	1.485Gbps
POWER CONSUMPTION:	12VDC, 250mA
INCLUDED ACCESSORIES:	Power supply, mounting bracket
OPTIONS:	RK-3T 19" rack adapter
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.0kg (0.0lbs) approx
SHIPPING DIMENSION:	23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H
SHIPPING WEIGHT:	0.6kg (1.4lbs) approx