

VM-24HC

2x1:4 Compact HDMI Switchable DA

| HDMI | HDCP Compliant



The VM-24HC is a high-performance switcher and distribution amplifier for HDMI signals. The unit accepts one of two HDMI inputs and distributes the selected signal to four HDMI outputs

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphics channel)

HDTV Compatible

HDCP Compliant

EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

EDID Handling - Acquires the EDID from one output, from all connected outputs (auto-mix) or uses a default EDID

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

HDMI Support - With Deep Color, x.v.Color™, up to 7.1 Uncompressed Audio Channels 3D Pass-Through

Flexible Control Options - Front panel, IR remote & RS-232

Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



TECHNICAL SPECIFICATIONS

INPUTS: 2 HDMI connectors

OUTPUTS: 4 HDMI connectors

MAX. DATA RATE: 6.75Gbps (2.25Gbps per graphic channel)

HDMI STANDARD:

COMPLIANCE WITH Supports HDMI and HDCP

CONTROLS: EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS-232, IR

INDICATORS: POWER, IR, OUTPUT LEDs

POWER 5V DC, 1.1A

CONSUMPTION:

OPERATING 0° to +40°C (32° to 104°F)

TEMPERATURE:

STORAGE -40° to $+70^{\circ}$ C (-40° to 158° F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

Accessories Included Power supply, IR remote control transmitter (upon request)

Product Dimensions 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H

Product Weight 0.9kg (1.9lbs) approx

Shipping Dimensions 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H

Shipping Weight 1.4kg (3.0lbs) approx



