

## VM-30AVB

1:3 Composite Video & Stereo Audio Distribution Amplifier



The VM-30AVB is a compact distribution amplifier for composite or SDI video and unbalanced stereo audio signals. It provides controls to compensate for signal losses inherent in long cable runs

## **FEATURES**

High Bandwidth - 430MHz at -3dB Video on BNC Connectors Audio Level Control Level (Gain) and EQ (Peaking) Controls

 $\label{eq:compact} \textbf{Desktop Size} \text{ - Compact size. Two units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter}$ 



## **TECHNICAL SPECIFICATIONS**

INPUTS: 1 video, 1 Vpp/75 $\Omega$  on a BNC connector; 1 audio stereo, 1Vpp/70k $\Omega$  on RCA

connectors

**OUTPUTS**: 3 video, 1 Vpp/75 $\Omega$  on BNC connectors; 3 audio stereo, 1Vpp/150 $\Omega$  on RCA

connectors

MAX. OUTPUT

LEVEL:

Video: 2Vpp; audio: 5.4Vpp

BANDWIDTH (-3dB): Video: 430MHz, audio: 100kHz

DIFF. GAIN: 0.04%

DIFF. PHASE: 0.07Deg

K-FACTOR: 0.05%

S/N RATIO: Video: 73dB, audio: 83dB

CONTROLS: Video level: -1.1 to +1.8dB, EQ.: 0 to +4.6dB @5.8MHz; Audio level: -66 to +16dB

COUPLING: AC

AUDIO THD+NOISE: 0.3%

AUDIO 2nd HARMONIC: 0.02%

POWER

**INCLUDED** 

12V DC, 50mA typical

CONSUMPTION:

ACCESSORIES:

OPTIONS: RK-1 19" rack adapter

**PRODUCT** DIMENSION: 16.30cm x 12.00cm x 4.40cm (6.42" x 4.72" x 1.73") W, D, H

12V DC power supply, brackets for stacking multiple units

PRODUCT WEIGHT: 0.6kg (1.3lbs) approx

SHIPPING DIMENSION: 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H

SHIPPING WEIGHT: 1.1kg (2.4lbs) approx

