

VP-100A

Computer Graphics Video to RGBHV & Audio Format Converter













The VP-100A is a high-performance format converter for computer graphics video and stereo audio signals. It converts a computer graphics video signal on a 15-pin HD connector to an RGBHV video signal on BNC connectors and unbalanced stereo on a 3.5mm connector to balanced stereo audio on a terminal block connector.

FEATURES

- High Bandwidth 430MHz (-3dB).
- HDTV Compatible.
- Horizontal and Vertical Sync Shift Control.
- EQ (Peaking) Control.
- Looping Input.
- ID Bit Control.
- Left and Right Audio Gain Controls.
- Desktop Size Compact Size. 2 units can be mounted side-by-side in a 1U rack space with the optional RK-1 adapter.

TECHNICAL SPECIFICATIONS

INPUT: Video: 1 XGA on 15-pin HD (F) connector; 1 XGA on 15-pin HD (F) loop; Audio: 1 unbalanced

stereo on 3.5mm mini-jack.

OUTPUTS: Video: R, G, B, Hs, Vs, Cs on BNC double connectors; Audio: 1 balanced stereo audio on a

5-pin terminal block connector.

MAX. OUTPUT LEVEL: Video: 2Vpp; Audio: 27Vpp.

BANDWIDTH (-3dB): Video: 430MHz; Audio: >100kHz.

DIFF. GAIN: 1.3%.
DIFF. PHASE: 0.35Deg.
K-FACTOR: <0.05%.

S/N RATIO: Video: 79dB; Audio: 70dB. CONTROLS: 0 to +5.3dB EQ. @50MHz.

COUPLING: Video: DC; Audio: Input: AC, Output: DC.

AUDIO THD + NOISE: 0.052%. AUDIO 2nd HARMONIC: 0.004%.

POWER 230V AC, 50/60Hz (115V, USA), 6VA.

CONSUMPTION:

DIMENSIONS: 22cm x 18cm x 4.5cm (8.7" x 7" x 1.7") W, D, H.

WEIGHT: 1.3kg (2.9lbs) approx.

INCLUDED Power cord.

ACCESSORIES:

OPTIONS: RK-1 19" rack adapter.

