

VP-14xl

RS-232 Port Extender/Converter



The VP-14xl is a port extender for RS-232, RS-485 or USB command signals. The unit converts the incoming commands to three RS-232 outputs

FEATURES

Hardware or Software Mode Operation DIP-Switch Controls - For HW source, SW addressing and baud rate



TECHNICAL SPECIFICATIONS

INPUT:	1 RS-232 on 9-pin D-sub (F) connector; 1 RS-485 on 3-pin removable terminal block; 1 USB Type B connector
OUTPUTS:	2 RS-232 on 9-pin D-sub (M) connectors, 1 RS-232 on 3-pin removable terminal block
BAUD RATE:	1200 to 115200bps
OPERATING MODES	: Hardware and software
USB COMPLIANCE:	1.1
CONTROLS:	DIP-switches
POWER CONSUMPTION:	5V DC, 130mA
INCLUDED ACCESSORIES:	Power supply, mounting bracket
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.6kg (1.2lbs) approx
OPTIONS:	RK-3T 19" rack adapter

