



VS-4FW

4-Port FireWire® Repeater/HUB



The VS-4FW is a high-performance bidirectional hub/repeater for 6-pin FireWire® (IEEE 1394) signals. It increases the number of ports available and/or extend the distance of FireWire® cable runs

FEATURES

Cascading Operation - Multiple units can be cascaded to create a FireWire® system with up to 63 ports

Range - Doubles FireWire® cable range from 4.5m (14.75ft) to 9m (29.5ft). Multiple units can be cascaded to extend the range to up to 72m (236ft)

Hot Swapping - Supports plug and play

Transfer Rates - 100, 200, and 400Mbps

ESD Protection - Incorporates Kramer's Spark-Guard Pro™ signal protection circuitry to help protect against EDS (electrostatic discharge) which can damage digital equipment

Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	VS-4FW: Four 6-pin serial 1394 Ports
TRANSFER RATE:	100/200/400Mbps
STANDARDS:	IEEE 1394-1995, P1394a
POWER CONSUMPTION:	12V DC, 200mA
INCLUDED ACCESSORIES:	12V DC power supply ,mounting bracket, one 6-pin to 6-pin connector cable
OPTIONS:	RK-3T 19" rack adapter
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.1kg (0.3lbs) approx
SHIPPING DIMENSION:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx

