



KRAMER

VS-6464DN-EM

8x8 to 64x64 Modular Multi-Format Managed
Digital Matrix Switcher

| DVI | Ethernet - RJ-45 | HDCP Compliant
| Kramer Core



VS-6464DN-EM is a high-performance 8x8 to 64x64 modular matrix switcher chassis for AV signals. The unit is a multi-format digital switcher, populated from 8x8 to 64x64 in increments of eight inputs and/or eight outputs. The chassis includes two power supplies with an optional third for redundancy, a control module and a test module that can monitor and test any input and output in the matrix. VS-6464DN-EM supports a wide variety of input and output cards for different AV signals

FEATURES

Kramer Core™ - FLEXIBLE INFRASTRUCTURE CONVERSION! Copper, Fiber or Twisted Pair – all can be used at the same time, according to input/output module selection. The matrix receives signals from compatible Kramer transmitters, automatically converts between available infrastructure options and sends the signals to compatible Kramer receivers. Kramer Core™ solution is the ultimate in versatility!

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel) when using compatible cards

Kramer Network Management - Automatic discovery through the network, FW upgrade management for matrix and cards, identify card type and location and indicate card status(module ID, actual firmware versions), matrix switching, specified card features configuration (for example, volume levels on audio cards), Store and Recall of predefined switching scenarios, integrated Maestro automation, and more

HDTV Compatible

HDCP Compliant - With DVI (HDCP) and HDMI modules

HDMI Support

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

Optional Fast Switching Support - For fraction of a second switching

Modular & Easily Configurable Platform - Input or output module types can be mixed and added in increments of 8 from 8x8 up to 64x64

Protocol 3000 Support

Flexible Configuration - To disable HDCP support and convert between HDMI and DVI

Default EDID - For each input

EDID Capture - Copies and stores the EDID from a display device

Take Button - Executes multiple switches all at once

Memory Locations - Stores multiple switches as presets to be recalled and executed as needed

Built-in Test Pattern Module - With 4 output resolutions for troubleshooting video problems and additional monitor port with audio embedding and de-embedding

Front Panel Lockout

Optional Redundant Power Supply - Hot-swappable

Modular Cooling System - 2 easily replaceable, low-noise, hot-swappable fan racks

Flexible Control Options - Front panel, IR remote (available upon request) , RS-232, Ethernet, mini USB port for communicating with unit and FW upgrade, in/out audio jacks for unit testing, and reset button for convenient unit reset (for future use)

Worldwide Power Supply - 100-240V AC




KRAMER

TECHNICAL SPECIFICATIONS

INPUTS:	8 to 64 (in increments of 8) of various inputs See ACCESSORIES & RELATED PRODUCTS
OUTPUTS:	8 to 64 (in increments of 8) of various outputs See ACCESSORIES & RELATED PRODUCTS
Video	Max. Data Rate 6.75Gbps (2.25Gbps per graphic channel) depending on the cards used Max. Resolution Up to UXGA; 1080p, 1920x1200 Standards Compliance Supports DVI 1.0
CONTROLS:	Front panel buttons, infrared remote control transmitter, RS-232, Ethernet, mini USB port, in/out audio testing jacks, reset button (for future use)
SWITCHING:	Confirm or At Once for immediate switching
Power	Source 100-240V AC, 50/60Hz Consumption 330VA
Accessories	Included Power cord, IR remote control transmitter
Product Dimensions	48.30cm x 36.00cm x 44.00cm (19.02" x 14.17" x 17.32") W, D, H
Product Weight	24.0kg (52.9lbs) approx
Shipping Dimensions	64.20cm x 57.00cm x 52.80cm (25.28" x 22.44" x 20.79") W, D, H
Shipping Weight	25.8kg (56.9lbs) approx





Control Computer

Control Computer

Computer Graphics Source

DVI Display

Computer Graphics Source

Plasma Display