

VS-66HN

6x6 HDMI Matrix Switcher



The VS-66HN is a high-performance matrix switcher for HDMI signals. It reclocks and equalizes the signal and can route any input to any or all outputs simultaneously

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel) HDTV Compatible

HDCP Compliant

HDMI Support - HDMI support for Deep Color, x.v.Color™, Dolby® TrueHD, Dolby Digital Plus, DTS-HD®, and linear PCM 7.1 surround sound

3D Pass-Through

Kramer Equalization & re-Klocking[™] Technology - Rebuilds the digital signal to travel longer distances

EDID Capture - Copies and stores the EDID from a display device

Output Disconnect - For each output

Front Panel Control Lockout

Memory Locations - Stores multiple switches as presets to be recalled and executed when needed Flexible Control Options - Front panel, IR remote, RS-232 (K-Router Plus™ Windows®-based software is included), Ethernet (Windows®-based Ethernet Configuration Manager & Virtual Serial Port Manager is included)

Worldwide Power Supply - 100-240V AC

Standard 19" Rack Mount Size - 1U. Rack "ears" included



TECHNICAL SPECIFICATIONS

INPUTS:	6 HDMI connectors
OUTPUTS:	6 HDMI connectors
BANDWIDTH:	6.75Gbps (2.25Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	HDMI and HDCP
RESOLUTION:	Up to UXGA; 1080p
POWER CONSUMPTION:	100-240V AC, 50/60Hz, 40VA
CONTROLS:	Front panel buttons, infrared remote control transmitter, RS-232, Ethernet
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Power cord, IR transmitter, rack "ears"
OPTIONS:	External remote IR receiver cable
PRODUCT DIMENSION:	19" x 14.17 x 1U (43.6cm x 36.00cm 22.15cm) W, D, H
PRODUCT WEIGHT:	2.3kg (5.1lbs) approx
SHIPPING DIMENSION:	66.00cm x 54.50cm x 60.00cm (25.98" x 21.46" x 23.62") W, D, H
SHIPPING WEIGHT:	3.4kg (7.4lbs) approx