

VS-801USB

8x1 USB 2.0 Switcher

| Ethernet - RJ-45



FEATURES

High-Speed USB - Ver 2.0 Flexible Control Options - Front panel buttons, RS-232 and Ethernet via K-SINGLE control application software, remote contact closure, IR remote (included) Firmware Upgrade - Via RS-232 using K-UPLOAD application software Compact MegaTOOLS™ - 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter



TECHNICAL SPECIFICATIONS

DEVICE PORTS:	8 USB, type A
HOST PORT:	1 USB, type B
CONTROL:	Front panel buttons, IR remote control, RS-232, Ethernet, remote contact closure terminal block
POWER CONSUMPTION:	5V DC, 150mA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Power supply, bracket installation kit, 1m hi-speed USB cable
OPTIONS:	RK-T2B 19" rack adapter
PRODUCT DIMENSION:	18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H
PRODUCT WEIGHT:	0.4kg (1.0lbs) approx
SHIPPING DIMENSION:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
SHIPPING WEIGHT:	1.1kg (2.4lbs) approx

